




SPECIFICATIONS 
DIELECTRIC STRENGTH: AC250V /1MIN
RATING:DC12V,50mA MAX
CONTACT RESISTANCE:100mΩ MAX
INSULATION RESISTANCE:100MΩ MIN
OPERATING LIFE:30,000 CYCLES
OPERATING FORCE:250gf±50gf

MATERIALS
BASE:LCP,NATURAL
TERMINAL:BRASS,SILVER PLATED
CONTACT:STAINLESS STEEL,SILVER PLATED
COVER:BRASS
ACTUATOR:LCP

ORDER INFORMATION



Top View
Recommended PCB Layout
(PCB TOLERANCE ±0.05)



	REC2507000039	Willy	2025/07/07
	BPM 20250108003	John	2025/04/28
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


懽德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TACT SWITCH SMT R/A TYPE				頁數 Page	1/1
品號 PART NO.	6STMR04-XXXXXXXXXA01				繪圖 DRAWN	JOHN 2025/06/12
圖號 DRAWING NO.	GN162-JH387	版本 REV.	B	核對 CHECKED	JOSH 2025/06/12	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2025/06/12	
公差 TOLERANCE	4<L≤16 ±0.3 L≤4 ±0.2	單位 UNIT	mm	THIRD ANGLE PROJECTION		