

STANDARD: UL 5 T
 RATED VOLTAGE: 300V
 RATED CURRENT: 25A
 CONTACT RESISTANCE: 20mΩ
 WITHSTANDING VOLTAGE: AC 1600V FOR ONE MIN
 INSULATION RESISTANCE: 500MΩ/DC500V
 WIRE RANGE: 22-12AWG

5 T B 1 0 0 S - 5 5 C E X X X L X - W 1

100
PITCH:10.0mm

SERIES No.

POLES
(02-22P)

B:BLACK




A:TRAY
B:BAG

MECHANICAL

TEMP. RANGE: -40°C ~ +105°C
TORQUE: 1.2Nm
MAX SOLDERING: +260°C, FOR 5 SEC

MATERIAL

HOUSING: NYLON66, UL94V-0
SCREWS: STEEL, M4 STEEL Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)

linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/12/04
 x2	ECN NO:201211 Revise the PART NO.	Alice	2020/12/31
 x1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 10.0mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB100S-55CEXXXLX-W1			繪圖 DRAWN	Eric 2019/01/09	
圖號 DRAWING NO.	GN011-EA525	版本 REV.	E	核對 CHECKED	Josh 2019/01/09	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/09	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		