


HOUSING: PBT, UL94V-0
SCREWS: M4 STEEL, Ni PLATED
TORQUE: 1.8N.m

OPERATING TEMPERATURE: -40°C~130°C
SOLDERING TEMPERATURE: 260°C/5SEC
CONTACT RESISTANCE: 20mΩ
INSULATION RESISTANCE: 1000MΩ/DC500V

UL/CUL

RATED VOLTAGE (V)	300
RATED CURRENT (A)	30
WITHSTANDING VOLTAGE	1600V (1MIN)
WIRE RANGE SOLID/STRANDED (AWG)	22-10

NOTE
 SMBOL "03" MEANS SERIAL AS ORDER INFORMATION SHOWN



General Tolerances										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	EasyFlow No.:202401240001	Randy	2024/05/20
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

5 T B 1 1 0 N - J 1 0 E X X X L X - 0 3




110:
PITCH11.0mm

SERIES NO.

NO OF POLES TOTAL
(02~15)

B:BLACK

B:BAG



品名 TITLE	TERMINAL BLOCK BARRIER 11.0mm				頁數 Page	1/1
品號 PART NO.	5TB110N-J10EXXXLX-03			繪圖 DRAWN	RANDY 2024/05/20	
圖號 DRAWING NO.	GN011-RD503	版本 REV.	A	核對 CHECKED	JOSH 2024/05/20	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2024/05/20	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		