

B **E**

ORDER INFORMATION

5 T B 1 1 0 S - 6 5 C E X X X L X - W 1

110
PITCH:11.0mm

SERIES No.





POLES
(02-24P)

B:BLACK

A:TRAY
B:BAG

TEMP. RANGE: -40°C ~ +105°C
TORQUE: 1.2Nm
MAX SOLDERING: +260°C, FOR 5 SEC

HOUSING: NYLON66, UL94V-0
SCREWS: STEEL, M4 STEEL Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/12/04
 x2	ECN NO:201211 Revise the PART NO	Alice	2021/01/04
 x1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/09
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 11.0mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB110S-65CEXXXLX-W1			繪圖 DRAWN	Eric 2019/01/10	
圖號 DRAWING NO.	GN011-EA531	版本 REV.	E	核對 CHECKED	Josh 2019/01/10	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/10	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		

AMTEK 糧德

2024.12.27

Released DCC