


ELECTRICAL

STANDARD: UL
RATED VOLTAGE: 300V
RATED CURRENT: 20A
CONTACT RESISTANCE:20mΩ
INSULATION RESISTANCE: 500MΩ / DC 500V
WITHSTANDING VOLTAGE: AC 1600V FOR ONE MINUTE
WIRE RANGE:22~14AWG

ORDER INFORMATION



AMTEK 糧德

2024.12.27





Released DCC

MECHANICAL

TEMP. RANGE: -40°C ~ +105°C
TORQUE:0.5Nm
MAX SOLDERING: +260°C, FOR 5 SEC

MATERIAL

HOUSING: NYLON66, UL94V-0
SCREWS: STEEL, M3 STEEL Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

ECN NO:240348 Revise the drawing	Gaby	2024/12/03
ECN NO:201211 Revise the PART NO	Alice	2021/01/04
ECN NO:200718 Revise the Tolerance	Alice	2020/11/12
REV.	ECN NO. OR DESCRIPTION	REVISED DATE


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 7.62mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB762S-25CEXXXLX-W1				繪圖 DRAWN	Kilin 2017/09/12
圖號 DRAWING NO.	GN011-KL039	版本 REV.	E	核對 CHECKED	Carol 2017/09/12	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2017/09/12	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		