

ELECTRICAL 
STANDARD: UL
RATED VOLTAGE: 300V
RATED CURRENT: 15A
CONTACT RESISTANCE: 20mΩ
WITHSTANDING VOLTAGE: AC 1600V FOR ONE MIN
INSULATION RESISTANCE: 500MΩ/DC500V
WIRE RANGE: 22-14AWG

ORDER INFORMATION

5

T

B

7

6

2

S

-

2

8

C

N

X

X



X

L

X

-



W

1

762

PITCH:7.62mm

SERIES No.






POLES
(02-22P)

B:BLACK

A:TRAY
B:BAG

MECHANICAL
TEMP. RANGE: -40°C ~ +105°C
TORQUE: 0.5Nm
MAX SOLDERING: +260°C, FOR 5 SEC

MATERIAL
HOUSING: NYLON66, UL94V-0
SCREWS: STEEL, M3 STEEL Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED
COVER: PC, UL94V-2



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	BPM 20250327006	Willy	2025/03/27
	ECN NO:240348 Revise the drawing	Gaby	2024/12/05
	ECN NO:201211 Revise the PART NO	Alice	2021/01/04
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 7.62mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB762S-28CNXXXLX-W1				繪圖 DRAWN	Eric 2019/01/10
圖號 DRAWING NO.	GN011-EA534	版本 REV.	F	核對 CHECKED	Josh 2019/01/10	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/10	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		