

ELECTRICAL

STANDARD: UL
RATED VOLTAGE: 300V
RATED CURRENT: 15A
CONTACT RESISTANCE: 20mΩ
WITHSTANDING VOLTAGE: AC 1600V FOR ONE MIN
INSULATION RESISTANCE: 500MΩ/DC500V
WIRE RANGE: 22-12AWG

ORDER INFORMATION





5	T	B	8	2	5	S	-	3	5	H	E	X	X	X	L	X	-	W	1
825 PITCH:8.25mm							SERIES No.			POLES (02-24P)			B:BLACK			A:TRAY B:BAG			

MECHANICAL

TEMP. RANGE: -40°C ~ +105°C
TORQUE: 0.5Nm
MAX SOLDERING: +260°C ,FOR 5 SEC

MATERIAL

HOUSING:NYLON66, UL94V-0
SCREWS:STEEL,M3 STEEL Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)




linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

E	ECN NO:240348 Revise the drawing	Gaby	2024/12/03
Dx2	ECN NO:201211 Revise the PART NO	Alice	2021/01/04
Cx1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/30
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	TERMINAL BLOCK BARRIER 8.25mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB825S-35HEXXXLX-W1				繪圖 DRAWN	Gary 2019/01/08
圖號 DRAWING NO.	GN011-GB774	版本 REV.	E	核對 CHECKED	Josh 2019/01/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/08	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		