



WG DIELECTRIC VOLTAGE: AC 1600V FOR ONE MINUTE

5	T	B	8	2	5	S	-	3	S	G	N	X	X	X	L	X	-	W	1
			825 PITCH:8.25mm				SERIES No.			No. OF POLES TOTAL (05,07,08,09P)			B:BLACK			B:BAG A:TRAY			





TORQUE:0.5N.m

PIN HEADER: COPPER ALLOY, Sn PLATED



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2025/02/13
	ECN NO:201211 Revise the PART NO	Alice	2021/01/05
	ECN NO:200718 Revise the Tolerance	Alice	2020/11/30
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 8.25mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB825S-3SGNXXXLX-W1			繪圖 DRAWN	ROY 2019/01/04	
圖號 DRAWING NO.	GN011-R1115	版本 REV.	E	核對 CHECKED	JOSH 2019/01/04	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2019/01/04	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		