

ELECTRICAL  

STANDARD: UL

RATED VOLTAGE: 300V

RATED CURRENT: 20A

CONTACT RESISTANCE: 20mΩ

WITHSTANDING VOLTAGE: AC 1600V FOR ONE MIN

INSULATION RESISTANCE: 500MΩ/DC500V

WIRE RANGE: 22-12 AWG

ORDER INFORMATION

5 T B 9 5 0 R - 4 5 R N X X X L X - W 1

950
PITCH:9.50mm

SERIES No.

POLES
(02-24P)

B:BLACK

A:TRAY
B:BAG

MECHANICAL

TEMP. RANGE: -40°C ~ +105°C

TORQUE: 1.2Nm





MAX SOLDERING: +260°C, FOR 5 SEC

MATERIAL

HOUSING: NYLON66, UL94V-0

SCREWS: STEEL, M4 STEEL Ni PLATED

PIN HEADER: COPPER ALLOY, Sn PLATED




RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∕	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	to 10	to 100	to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/12/04
	ECN NO:200718 Revise the Tolerance & ECN NO:201211 Revise the PART NO.	Alice	2020/12/22
	ECN 200102: Remove the IEC	David	2020/06/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	TERMINAL BLOCK BARRIER 9.50mm DIP R/A TYPE				頁數 Page	1/1
品號 PART NO.	5TB950R-45RNXXLX-W1				繪圖 DRAWN	Eric 2019/01/11
圖號 DRAWING NO.	GN011-EA565	版本 REV.	D	核對 CHECKED	Josh 2019/01/11	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/11	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		