


ELECTRICAL 
RATED VOLTAGE: 300V
RATED CURRENT: 20A
CONTACT RESISTANCE:20mΩ
INSULATION RESISTANCE: 500MΩ / DC 500V
WIRE RANGE: 22-12AWG
DIELECTRIC VOLTAGE: AC 1600V FOR ONE MINUTE

ORDER INFORMATION







MECHANICAL

TEMP RANGE: -40°C ~ +105°C
SOLDERING: +260°C ,FOR 5 SEC
TORQUE:1.2N.m

MATERIAL

HOUSING: NYLON 66, UL94V-0
SCREWS: STEEL, M4.0 Ni PLATED
PIN HEADER: COPPER ALLOY, Sn PLATED
COVER: PC, UL94V-2



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2025/02/13
	ECN NO:200718 Revise the Tolerance & ECN NO:201211 Revise the PART NO.	Alice	2020/12/23
	ECN 200102: Remove the IEC	David	2020/06/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 9.50mm DIP R/A TYPE				頁數 Page	1/1
品號 PART NO.	5TB950R-46GNXXXLX-W1				繪圖 DRAWN	ROY 2019/01/03
圖號 DRAWING NO.	GN011-R1110	版本 REV.	D	核對 CHECKED	JOSH 2019/01/03	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2019/01/03	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		