

ELECTRICAL

RATED VOLTAGE: 300V

RATED CURRENT: 25A

CONTACT RESISTANCE: 20mΩ

INSULATION RESISTANCE: 500MΩ / DC 500V

WIRE RANGE: 22-12AWG

DIELECTRIC VOLTAGE: AC 1600V FOR ONE MINUTE

ORDER INFORMATION

5	T	B	9	5	0	S	-	6	G	G	N	X	X	X	L	X	-	W	1
950 PITCH:9.50mm								SERIES No.			No. OF POLES TOTAL (02~12P)			B:BLACK		B:BAG A:TRAY			

MECHANICAL

TEMP. RANGE: -40°C ~ +105°C

SOLDERING: +260°C, FOR 5 SEC

TORQUE: 1.2Nm


MATERIAL

HOUSING: NYLON 66, UL94V-0



SCREWS: M4 STEEL Ni PLATED

PIN HEADER: COPPER ALLOY, Sn PLATED

COVER: PC, UL94V-2



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∠	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△D	ECN NO:240348 Revise the drawing	Gaby	2025/02/19
△x3	ECN NO:200718 Revise the Tolerance & ECN NO:201211 Revise the PART NO.	Alice	2020/12/23
△x1	ECN 200102: Remove the IEC	David	2020/06/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK BARRIER 9.50mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TB950S-6GGNXXXLX-W1				繪圖 DRAWN	ROY 2019/01/02
圖號 DRAWING NO.	GN011-R1098	版本 REV.	D	核對 CHECKED	JOSH 2019/01/02	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2019/01/02	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		