

MATERIAL
HOUSING:NYLON66, UL94V-0
PIN:COPPER ALLOY,S_n PLATED

MECHANICAL
OPERATING TEMPERATURE:-40°C~+105°C
SOLDERING TEMPERATURE:260°C/5S

TECHNICAL DATA





UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	300	300
RATED CURRENT (A)	55	55	10
WIRE RANGE			
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC61984

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	1000	1000	1000
RATED CURRENT (A)	76	76	76
IMPULSE WITHSTANDING VOLTAGE (KV)	8.0	8.0	6.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)			

ORDER INFORMATION



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∕	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 100	to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

ECN NO:240348 Revise the drawing	Gaby	2024/11/18
ECN NO:200718 Revise the Dimension	Alice	2020/09/03
REV.	ECN NO. OR DESCRIPTION	REVISED DATE

Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 10.16mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TP101S-3VCNXXLX-01				繪圖 DRAWN	MIA 2018/01/24
圖號 DRAWING NO.	GN011-MC905	版本 REV.	C	核對 CHECKED	JOSH 2018/01/24	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/01/24	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		