

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 250V
Rated Current: 8A 7A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-16AWG 1.5 mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
Torque: 0.4Nm
Strip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
Wire guard: Stainless steel
Clamp: Phosphor bronze, Ni plated
Screw: M2.5 Steel, Zn plated

ORDER INFORMATION

5 T P 3 5 0 N -

5 K D E X X

E L

X - 0 1

Series No.

Poles
(02-24P)

E:Green




A:Tray
B:Bag



AMTEK 糧德

2020.09.09

Released DCC



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
	ECN NO:200718 Revise the Dimension	Alice	2020/09/04


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	3.5mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP350N-5KDEXXELX-01				繪圖 DRAWN	Eric 2018/11/27
圖號 DRAWING NO.	GN011-EA115		版本 REV.	B	核對 CHECKED	Josh 2018/11/27
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/11/27
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	