

HOUSING: NYLON66, UL94V-0
 SPRING: STAINLESS STEEL
 CLAMP: COPPER ALLOY, Sn PLATED
 BUTTON: POM, UL94-HB

5 T P 3 5 0 N - 5 N R E X X X L X - 0 1

350:
PITCH3.50mm

SERIES NO.

NO OF POLES TOTAL
(02~24)

E:GREEN

B:BAG




OPERATING TEMPERATURE:-40°C~+105°C
STRIPPING LENGTH:9-10mm

TECHNICAL DATA

UL/CUL


SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	8	-	8
WIRE RANGE SOLID/STRANDED (AWG)	24-16		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC 61984		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	160	320
RATED CURRENT (A)	8	8	8
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.5-1.5		



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	EasyFlow No.:202401240001	Gaby	2024/07/08
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	TERMINAL BLOCK PLUGGABLE 3.50mm				頁數 Page	1/1
品號 PART NO.	5TP350N-5NREXXLX-01			繪圖 DRAWN	GABY 2024/07/08	
圖號 DRAWING NO.	GN011-JH021	版本 REV.	A	核對 CHECKED	JOSH 2024/07/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2024/07/08	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		