

MATERIAL

HOUSING: NYLON66, UL94V-0
SPRING: STAINLESS STEEL
CLAMP: COPPER ALLOY, Sn PLATED
BUTTON: POM, UL94-HB

MECHANICAL

OPERATING TEMPERATURE: -40°C ~ +105°C
STRIPPING LENGTH: 9-10mm

TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	8	-	8
WIRE RANGE SOLID/STRANDED (AWG)	24-16		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC IEC 61984

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	160	320
RATED CURRENT (A)	8	8	8
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.5-1.5		




linear dimension (Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 10	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	EasyFlow No.: 202401240001	Gaby	2024/07/08
	ECN NO. OR DESCRIPTION	REVISED	DATE

ORDER INFORMATION

5	T	P	3	5	0	N	-	5	N	R	N	X	X	X	L	X	-	0	1
350: PITCH 3.50mm							SERIES NO.		NO OF POLES TOTAL (02~24)				E: GREEN		B: BAG				




懋德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 3.50mm				頁數 Page	1/1
品號 PART NO.	5TP350N-5NRNXXLX-01			繪圖 DRAWN	GABY 2024/07/08	
圖號 DRAWING NO.	GN011-JH020	版本 REV.	A	核對 CHECKED	JOSH 2024/07/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2024/07/08	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		