

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 8A 10A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ

MECHANICAL

Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: PA66, UL94V-0
 Pin header: Copper alloy, Sn plated

ORDER INFORMATION

5 T P 3 5 0 S -

5 G B E X X


E L X - 0 1

Series No.




Poles
(02-24P)

E:Green

A:Tray
B:Bag



P.C.B. LAYOUT



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
	ECN NO:200718 Revise the Dimension	Alice	2020/09/09



糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	3.5mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP350S-5GBEXXELX-01				繪圖 DRAWN	Eric 2018/11/29
圖號 DRAWING NO.	GN011-EA119		版本 REV.	B	核對 CHECKED	Josh 2018/11/29
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/11/29
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	