

ORDER INFORMATION

HOUSING: LCP, UL94V-0

PIN: COPPER ALLOY ,SN PLATED

MATERIAL

OPERATING TEMPERATURE: -40°C~+130°C

SOLDERING TEMPERATURE: 260°C/5S

TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	-
RATED CURRENT (A)	8	-	-
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC		IEC61984	
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	160	160
RATED CURRENT (A)	8	8	8
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5

NOTE

SYMBOL "02" MEANS SERIAL AS ORDER INFORMATION SHOWN

5 T P 3 5 0 S - E H 3 N X X X U X - 0 2





350:
PITCH3.50mm

SERIES NO.

NO OF PINS
TOTAL(06-72)

B:BLACK

X:BOX



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ± 0.05)

General Tolerances

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	BPM NO.:202401240001	Randy	2024/06/17
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 3.50mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TP350S-EH3NXXXUX-02			繪圖 DRAWN	Randy 2024/06/05	
圖號 DRAWING NO.	GN011-RD555	版本 REV.	A	核對 CHECKED	Josh 2024/06/05	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2024/06/05	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		