

MATERIAL

HOUSING: NYLON 66, UL94V-0
CLAMP: COPPER ALLOY, TIN PLATED
PARTITION: NYLON 66, UL94V-0
SPRING: STAINLESS STEEL
BUTTON: POM, UL94-HB
COVER: NYLON 66, UL94V-0
HOOK: NYLON 66, UL94V-0

SPECIFICATION

OPERATING TEMPERATURE: -40°C~105°C
STRIPPING LENGTH: 9-10mm




TECHNICAL DATA

SAFETY APPROVAL			
			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	8	-	8
WIRE RANGE	24-16		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC			
IEC 61984			
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	160	320
RATED CURRENT (A)	8	8	8
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION	0.2-1.5		
SOLID/FLEXIBLE (mm²)			

ORDER INFORMATION

5	T	P	3	8	1	N	-	5	G	B	F	X	X	X	L	X	-	0	1
381: PITCH 3.81mm						SERIES NO.		NO OF POLES TOTAL (04-48)				E: GREEN			B: BAG				



linear dimension(Tolerances Standard GB/T 14486-2008)									
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	+0.20	+0.30	+0.50	+0.70	±1.00	+1.30	+1.60	0.10	0.30

EasyFlow No.: 202401240001				Randy		2024/05/14	
REV.				ECN NO. OR DESCRIPTION		REVISED	
						DATE	



懋德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 3.81mm				頁數 Page	1/1
品號 PART NO.	5TP381N-5GBFXXXLX-01			繪圖 DRAWN	RANDY	
圖號 DRAWING NO.	GN011-RD474	版本 REV.	A	核對 CHECKED	JOSH	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH	
公差 TOLERANCE		單位 UNIT	mm	第三角 THIRD ANGLE PROJECTION		