

**MATERIAL**

HOUSING: NYLON66, UL94V-0  
COVER: NYLON66, UL94V-0  
PIN: COPPER ALLOY, Sn PLATED  
NUT: COPPER ALLOY, M2.5

**ORDER INFORMATION**

5 T P 3 8 1 S - 5 E H E X X X L X - 0 1

381  
PITCH: 3.81mm

SERIES No.

NO OF POLES TOTAL  
(04~48P)

E: GREEN

A: TRAY  
B: BAG

**MECHANICAL**





OPERATING TEMPERATURE: -40°C~+105°C  
SOLDERING TEMPERATURE: 260°C/5S

**TECHNICAL DATA**

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	8	-	8
WIRE RANGE SOLID/STRANDED (AWG)	-		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC61984		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	160	250
RATED CURRENT (A)	7	7	7
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm <sup>2</sup> )	-		



RECOMMENDED PCB LAOUT  
(PCB TOLERANCE ±0.05)



linear dimension (Tolerances Standard GB/T 14486-2008)

		over 6	over 10	over 30	over 60	over 100	over 160		over 10	over 100
variable range	to 6	to 10	to 30	to 60	to 100	to 160	to 10	to 100	to 100	to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/10/15
	ECN NO:220814 Revise the PART NO.	Tim	2022/09/16
	ECN NO:200718 Revise the Tolerance	Alice	2020/09/10
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

懋德精密有限公司  
Amtek Technology Co., Ltd.  
TEL: 886-2-2260-6878  
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 3.81mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TP381S-5EHXXXXLX-01			繪圖 DRAWN	ERIC 2018/12/17	
圖號 DRAWING NO.	GN011-EA304	版本 REV.	D	核對 CHECKED	JOSH 2018/12/17	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/17	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		