

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 450V
Rated Current: 10A 20A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-14AWG 2.5mm²

MECHANICAL


Temp. Range: -40°C ~ +105°C
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
Screws: M2.5 Steel, Zn plated
Clamp: Copper alloy, Sn plated
Wire guard: Stainless steel

ORDER INFORMATION

5	T	P	5	0	0	N	-	2	D	A	E	X	X	E	L	X	-	0	1
Series No.								Poles (02-24P)			E:Green			A:Tray B:Bag					



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ECN NO:200718 Revise the Tolerance

Alice

2020/09/10

REV.

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP500N-2DAEXXELX-01				繪圖 DRAWN	Eric 2018/12/03
圖號 DRAWING NO.	GN011-EA165		版本 REV.	B	核對 CHECKED	Josh 2018/12/03
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/03
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	