

MATERIAL
HOUSING: NYLON66, UL94V-0
COVER: NYLON66, UL94V-0
CLAMP: COPPER ALLOY, Ni PLATED
CAGE: COPPER ALLOY, M3/Ni PLATED
SCREW: STEEL, M3/Zn PLATED, TORQUE: 0.5N.m

MECHANICAL
OPERATING TEMPERATURE: -40°C~+105°C
STRIPPING LENGTH: 7~8mm

TECHNICAL DATA



UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE	28-12		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		


IEC			
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	250	320	630
RATED CURRENT (A)	10	10	10
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm²)	0.2-2.5		

ORDER INFORMATION



5	T	P	5	0	0	N	-	2	K	Z	N	X	X	X	L	X	-	0	1
500: PITCH 5.00mm							SERIES No.			NO OF POLES TOTAL (02~24)			E: GREEN			B: BAG			



2-3POS



4-7POS



8-24POS



linear dimension(Tolerances Standard GB/T 14486-2008)								—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/10/23
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/16
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	△ TERMINAL BLOCK PLUGGABLE 5.00mm				頁數 Page	1/1
品號 PART NO.	△ 5TP500N-2KZNXLLX-01				繪圖 DRAWN	Kilin 2017/09/26
圖號 DRAWING NO.	GN011-KL082	版本 REV.	C	核對 CHECKED	Jason 2017/09/26	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2017/09/26	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		