

MECHANICAL

TEMP.RANGE:-40°C~+130°C

MATERIAL

HOUSING: LCP, UL94V-0

PIN: COPPER ALLOY ,Sn PLATED

ORDER INFORMATION

5 T P 5 0 0 S - 2 T H N X X X U X - 0 1

500
PITCH:5.00mm

SERIES NO.

NO OF POLES TOTAL
(02-24)

B:BLACK

B:BAG


TECHNICAL DATA

UL/CUL

USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE SOLID/STRANDED (AWG)	-		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	250	320	400
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	4	4	4
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	-		



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)

General Tolerances

General Tolerances										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

BPM 202401240001

Gaby

2024/06/05

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 5.00mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TP500S-2THNXXXUX-01			繪圖 DRAWN	RANDY 2024/06/05	
圖號 DRAWING NO.	GN011-GY718	版本 REV.	A	核對 CHECKED	JOSH 2024/06/05	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2024/06/05	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		