


UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	12	-	10
WIRE RANGE SOLID/STRANDED (AWG)	24-16		
WITHSTANDING VOLTAGE	1600V (1MIN)		



IEC	III	III	II
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	320	320	630
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.2-1.5/0.2-2.5		

5 T P 5 0 8 N - 2 E G E X X X L X - 0 1

B:BAG




FOR 2 PINS, ONLY THIS
ONE IS AVAILABLE.



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	BPM 202401240001
REV.	ECN NO. OR DESCRIPTION



品名 TITLE	TERMINAL BLOCK PLUGGABLE 5.08mm				頁數 Page	1/1
品號 PART NO.	5TP508N-2EGEXXXLX-01			繪圖 DRAWN	Gaby 2024/05/27	
圖號 DRAWING NO.	GN011-GY704	版本 REV.	A	核對 CHECKED	Josh 2024/05/27	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2024/05/27	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		