

MATERIAL

HOUSING: NYLON66, UL94V-0
COVER: NYLON66, UL94V-0
PIN: COPPER ALLOY, Sn PLATED
SPRING: STAINLESS STEEL
BUTTON: POM, UL94-HB

MECHANICAL

OPERATING TEMPERATURE: -40°C~+105°C
STRIPPING LENGTH: 7~8mm

TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	10	-	10
WIRE RANGE	28-12		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC61984

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	320	320	630
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION	0.2-2.5		
SOLID/FLEXIBLE (mm ²)			






linear dimension (Tolerances Standard GB/T 14486-2008)								—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN NO:240348 Revise the drawing							Gaby	2024/11/14
△	ECN NO:230714 Revise the PART NO.							Gaby	2023/09/23
△x2	ECN NO:201215 Revise the PART NO.							Alice	2020/12/30
REV.	ECN NO. OR DESCRIPTION							REVISED	DATE

ORDER INFORMATION

5	T	P	5	0	8	N	-	2	K	G	N	X	X	X	L	X	-	0	1
508 PITCH: 5.08mm							SERIES No.			POLES (02-24P)			E: GREEN		A: TRAY B: BAG				




Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 5.08mm				頁數 Page	1/1
品號 PART NO.	5TP508N-2KGNXXXLX-01			繪圖 DRAWN	ERIC 2018/12/06	
圖號 DRAWING NO.	GN011-EA200	版本 REV.	E	核對 CHECKED	JOSH 2018/12/06	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/06	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		