

MATERIAL
HOUSING: NYLON66, UL94V-0
COVER: NYLON66, UL94V-0
PIN: COPPER ALLOY, Sn PLATED
SPRING: STAINLESS STEEL
BUTTON: POM, UL94-HB
SCREW: STEEL, M2.5/Zn PLATED

MECHANICAL
OPERATING TEMPERATURE: -40°C~+105°C
STRIPPING LENGTH: 7~8mm

TECHNICAL DATA

UL/CUL			
SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	10	-	10
WIRE RANGE	28-12		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC61984			
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	320	320	630
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION	0.2-2.5		
SOLID/FLEXIBLE (mm²)			



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing						Gaby	2024/11/14
	ECN NO:230714 Revise the PART NO.						Gaby	2023/09/23
	ECN NO:201215 Revise the PART NO.						Alice	2020/12/30
REV.	ECN NO. OR DESCRIPTION						REVISED	DATE

ORDER INFORMATION

5 T P 5 0 8 N - 2 K R E X X X L X - 0 1




508
PITCH:5.08mm

SERIES No.

POLES
(02-24P)

E:GREEN

A:TRAY
B:BAG



Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 5.08mm				頁數 Page	1/1
品號 PART NO.	5TP508N-2KREXXXLX-01				繪圖 DRAWN	Eric 2018/12/06
圖號 DRAWING NO.	GN011-EA196	版本 REV.	E	核對 CHECKED	Josh 2018/12/06	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/06	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		