

MATERIAL

HOUSING: NYLON66, UL94V-0

COVER: NYLON66, UL94V-0

CLAMP: COPPER ALLOY, Sn PLATED

CAGE: COPPER ALLOY, M3/Ni PLATED

SCREW1: STEEL, M3/Zn PLATED, TORQUE: 0.5N.m

SCREW2: STEEL, M2.5/Zn PLATED

ORDER INFORMATION

5 T P 5 0 8 N - K H M E X X X L X - 0 1

508
PITCH: 5.08mm

SERIES No.

POLES
(02-24P)

E: GREEN

A: TRAY
B: BAG

MECHANICAL

OPERATING TEMPERATURE: -40°C ~ +105°C

STRIPPING LENGTH: 7~8mm

TECHNICAL DATA


UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE	28-12		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC

IEC 61984

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	250	320	630
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION	0.2-2.5		
SOLID/FLEXIBLE (mm ²)			



linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN NO:240348 Revise the drawing	Gaby	2024/10/21
△	ECN NO:230714 Revise the PART NO.	Gaby	2023/09/23
△x2	ECN NO:201215 Revise the PART NO.	Alice	2020/12/30
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 5.08mm				頁數 Page	1/1
品號 PART NO.	5TP508N-KHMEXXXLX-01				繪圖 DRAWN	DAVID 2018/12/03
圖號 DRAWING NO.	GN011-EA151	版本 REV.	E	核對 CHECKED	JOSH 2018/12/03	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2018/12/03	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		