

MATERIAL

HOUSING: NYLON66, UL94V-0

COVER: NYLON66, UL94V-0

CAGE: COPPER ALLOY, M3/Ni PLATED

SCREW1: STEEL, M3/Zn PLATED, TORQUE: 0.5N.m

SCREW2: STEEL, M2.5/Zn PLATED

CLAMP: COPPER ALLOY, Sn PLATED

ORDER INFORMATION

5	T	P	7	5	0	N	-	2	K	B	E	X	X	X	L	X	-	0	1
750 PITCH: 7.50mm							SERIES No.			POLES (02-24P)			E: GREEN			A: TRAY B: BAG			

MECHANICAL

OPERATING TEMPERATURE: -40°C ~ +105°C

STRIPPING LENGTH: 7~8mm


TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE SOLID/STRANDED (AWG)	28-12		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	500	630	1000
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	6.0	6.0	6.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.2-2.5		



linear dimension (Tolerances Standard GB/T 14486-2008)								—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO: 240348 Revise the drawing	Gaby	2024/10/21
△x1	ECN NO: 200718 Revise the Tolerance	Alice	2020/09/25
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	△ TERMINAL BLOCK PLUGGABLE 7.50mm				頁數 Page	1/1
品號 PART NO.	△ 5TP750N-2KBEXXXLX-01			繪圖 DRAWN	Eric 2018/12/18	
圖號 DRAWING NO.	GN011-EA317	版本 REV.	C	核對 CHECKED	Josh 2018/12/18	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/18	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		