

HOUSING: NYLON66, UL94V-0
PIN: COPPER ALLOY, Sn PLATED
NUT: COPPER ALLOY, M2.5

5	T	P	7	5	0	S	-	2	E	V	E	X	X	X	L	X	-	0	1
750 PITCH:7.50mm							SERIES No.			NO. OF POLES (02~24P)			E:GREEN		B:BAG A:TRAY				

Released DCC





OPERATING TEMPERATURE:-40°C~+105°C
SOLDERING TEMPERATURE:260°C/5S

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE SOLID/STRANDED (AWG)	-		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC

SAFETY APPROVAL			
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	400	630	630
RATED CURRENT (A)	10	10	10
IMPULSE WITHSTANDING VOLTAGE (kV)	6.0	6.0	6.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	-		



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160	to 10	over 10 to 100	over 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

[illegible]

糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 7.50mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TP750S-2EVEXXXLX-01			繪圖 DRAWN	DAVID 2020/03/19	
圖號 DRAWING NO.	GN011-DV922	版本 REV.	C	核對 CHECKED	JOSH 2020/03/19	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2020/03/19	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		