

MATERIAL

HOUSING: NYLON66, UL94V-0
CLAMP: COPPER ALLOY, Sn PLATED
NUT: COPPER ALLOY, M2.5

MECHANICAL

OPERATING TEMPERATURE: -40°C~+105°C
SOLDERING TEMPERATURE: 260°C/5S

TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE			
SOLID/STRANDED (AWG)	-		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC 60944		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	500	630	1000
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	6.0	6.0	6.0
CONDUCTOR CROSS SECTION			
SOLID/FLEXIBLE (mm²)	-		

ORDER INFORMATION

5 T P 7 6 2 R - 2 E A E X X X L X - 0 1





762
PITCH: 7.62mm

SERIES No.

POLES
(02-16P)

E: GREEN

A: TRAY
B: BAG



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)

linear dimension(Tolerances Standard GB/T 14486-2008)							— □ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
△	ECN NO:240348 Revise the drawing	Gaby	2024/10/25
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/30



Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 7.62mm DIP R/A TYPE				頁數 Page	1/1
品號 PART NO.	5TP762R-2EAEXXLX-01				繪圖 DRAWN	ERIC 2018/12/05
圖號 DRAWING NO.	GN011-EA181	版本 REV.	C	核對 CHECKED	JOSH 2018/12/05	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/05	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		