

MATERIAL
HOUSING: NYLON66, UL94V-0
CLAMP: COPPER ALLOY, Sn PLATED

MECHANICAL
OPERATING TEMPERATURE: -40°C~+105°C
SOLDERING TEMPERATURE: 260°C/5S


TECHNICAL DATA

UL/CUL




SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	15	-	10
WIRE RANGE SOLID/STRANDED (AWG)	-		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC61984		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	500	630	1000
RATED CURRENT (A)	12	12	12
IMPULSE WITHSTANDING VOLTAGE (KV)	6.0	6.0	6.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	-		

ORDER INFORMATION



FOR 2 PINS,
ONLY THIS ONE IS AVAILABLE



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∕	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/10/25
	ECN NO:200718 Revise the Tolerance	Alice	2020/09/30
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PLUGGABLE 7.62mm DIP R/A TYPE				頁數 Page	1/1
品號 PART NO.	5TP762R-2EANXXLX-01			繪圖 DRAWN	MIA 2016/12/08	
圖號 DRAWING NO.	GN011-MC122	版本 REV.	C	核對 CHECKED	JONNY 2016/12/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	AARON 2016/12/08	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		