

HOUSING: NYLON66, UL94V-0
COVER: NYLON66, UL94V-0
BUTTON: POM, UL94-HB
PIN: COPPER ALLOY, Sn PLATED
SPRING: STAINLESS STEEL

5 T R 2 5 4 S - 2 1 1 N X X X L X - W 1

254
PITCH:2.54mm

SERIES No.

POLES
(01-30)

G:GRAY


A:TRAY
B:BAG

OPERATING TEMPERATURE:-40°C~+105°C
SOLDERING TEMPERATURE:260°C/5S
STRIPPING LENGTH:11mm




△D

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	150	-	-
RATED CURRENT (A)	5	-	-
WIRE RANGE SOLID/STRANDED (AWG)	26-18		
WITHSTANDING VOLTAGE	1300V (1MIN)		

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	63	160	320
RATED CURRENT (A)	6	6	6
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.2-0.5		



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2025/02/13
 x2	ECN NO:201126 Revise the PART NO.	Alice	2020/12/11
 x1	ECN NO:200718 Revise the Tolerance	Alice	2020/10/05
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PCB SPRING 2.54mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TR254S-211NXXLX-W1			繪圖 DRAWN	ERIC 2018/12/21	
圖號 DRAWING NO.	GN011-EA371	版本 REV.	D	核對 CHECKED	JOSH 2018/12/21	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/21	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		