

MATERIAL
HOUSING: NYLON 66, UL94V-0
CONTACTOR: COPPER ALLOY, TIN PLATED
SPECIFICATION
OPERATING TEMPERATURE: -40°C~105°C
SOLDERING TEMPERATURE: 260°C/5SEC
STRIPPING LENGTH: 9-10mm





TECHNICAL DATA
UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	12	-	10
WIRE RANGE	20-12		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC60947-7-4		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	320	320	630
RATED CURRENT (A)	32	32	32
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm²)	0.2-4.0		

ORDER INFORMATION

5	T	R	5	0	0	L	-	2	4	2	N	X	X	X	L	X	-	0	1
500: PITCH 5.00mm							SERIES NO.			NO OF POLES (01-24)			G:GRAY			A:TRAY			



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)

linear dimension(Tolerances Standard GB/T 14486-2008)								—	∕	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO.240824 Revise the drawing	Benson	2024/10/01
	EasyFlow No.:202401240001	Randy	2024/03/08
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

糧德精密有限公司

品名 TITLE	TERMINAL BLOCK PCB SPRING 5.00mm DIP ANGLED TYPE				頁數 Page	1/1
品號 PART NO.	5TR500L-242NXXXLX-01			繪圖 DRAWN	Randy 2024/03/08	
圖號 DRAWING NO.	GN011-RD356	版本 REV.	B	核對 CHECKED	Josh 2024/03/08	
客戶品號 CUSTOMER P/N		比例 SCALE	1:1	承認 APPROVED	Josh 2024/03/08	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		