

MATERIAL
HOUSING: LCP, UL94V-0
PIN: COPPER ALLOY, Sn PLATED

ORDER INFORMATION

5 T R 5 0 0 R - 2 1 2 N X X X U X - 0 1

500
PITCH: 5.00mm

SERIES No.

POLES
(02-24P)

B: BLACK

A: TRAY





MECHANICAL
OPERATING TEMPERATURE: -40°C~+130°C
SOLDERING TEMPERATURE: 260°C/10S
STRIPPING LENGTH: 7~8mm

TECHNICAL DATA

UL/CUL

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	10	-	10
WIRE RANGE	24-16		
SOLID/STRANDED (AWG)			
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC	IEC 60917-4		
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	250	320	500
RATED CURRENT (A)	17.5	17.5	17.5
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION	0.2-1.5		
SOLID/FLEXIBLE (mm²)			



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ±0.05)



linear dimension (Tolerances Standard GB/T 14486-2008)								—	∠	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	to 10	over 10 to 100	over 100 to 250
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO.: 240348 Revise the drawing	Gaby	2024/11/19
	ECN NO.: 230831 Revise the Electrical	Gaby	2023/09/14
	ECN NO.: 230714 Revise the PART NO	Benson	2023/08/29
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PCB SPRING 5.00mm DIP R/A TYPE				頁數 Page	1/1
品號 PART NO.	5TR500R-212NXXXUX-01				繪圖 DRAWN	ERIC 2018/12/27
圖號 DRAWING NO.	GN011-EA407	版本 REV.	G	核對 CHECKED	JOSH 2018/12/27	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/27	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		