

HOUSING: NYLON66, UL94V-0
PIN: COPPER ALLOY, Sn PLATED

5 T R 5 0 8 L -




OPERATING TEMPERATURE:-40°C~+105°C
STRIPPING LENGTH:5~6mm

TECHNICAL DATA

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	10	-	10
WIRE RANGE SOLID/STRANDED (AWG)	28-12		
WITHSTANDING VOLTAGE	1600V (1MIN)		

1E060947-7-4

OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	250	320	630
RATED CURRENT (A)	18	18	18
IMPULSE WITHSTANDING VOLTAGE (KV)	4.0	4.0	4.0
CONDUCTOR CROSS SECTION SOLID/FLEXIBLE (mm ²)	0.2-2.5		



RECOMMENDED PCB LAOUT
(PCB TOLERANCE ± 0.05)

linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/11/21
	ECN NO:230714 Revise the PART NO.	Randy	2023/09/23
	ECN NO:220814 Revise the PART NO.	Tim	2022/09/16
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PCB SPRING 5.08mm DIP ANGLED TYPE				頁數 Page	1/1
品號 PART NO.	5TR508L-4T4NXXXLX-01			繪圖 DRAWN	ERIC 2018/12/26	
圖號 DRAWING NO.	GN011-EA399	版本 REV.	F	核對 CHECKED	JOSH 2018/12/26	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JASON 2018/12/26	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		

2025.01.03

Released DCC