


ORDER INFORMATION

MATERIAL
HOUSING: NYLON66, UL94V-0
CAGE: COPPER ALLOY, M2/Ni PLATED
SCREW: STEEL, M2/Zn PLATED, TORQUE: 0.2N.m
HEADER PIN: COPPER ALLOY, Sn PLATED







MECHANICAL
OPERATING TEMPERATURE: -40°C~+105°C
SOLDERING TEMPERATURE: 260°C/5S
STRIPPING LENGTH: 4~5mm

TECHNICAL DATA

SAFETY APPROVAL			
USE GROUP	B	C	D
RATED VOLTAGE (V)	300	-	300
RATED CURRENT (A)	10	-	10
WIRE RANGE	28-16		
SOLID/STRANDED (AWG)	28-16		
WITHSTANDING VOLTAGE	1600V (1MIN)		

IEC

SAFETY APPROVAL			
OVERVOLTAGE CATEGORY	III	III	II
CONTAMINATION CLASS	3	2	2
RATED VOLTAGE (V)	160	200	400
RATED CURRENT (A)	13.5	13.5	13.5
IMPULSE WITHSTANDING VOLTAGE (KV)	2.5	2.5	2.5
CONDUCTOR CROSS SECTION	0.5-1.0		
SOLID/FLEXIBLE (mm ²)	0.5-1.0		



RECOMMENDED PCB LAOUT (PCB TOLERANCE ±0.05)

	linear dimension (Tolerances Standard GB/T 14486-2008)							—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:240348 Revise the drawing	Gaby	2024/11/28
	ECN NO:200718 Revise the Tolerance	Alice	2020/12/04
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK PCB SCREW 3.50mm DIP V/T TYPE				頁數 Page	1/1
品號 PART NO.	5TS350S-38HNXXXLX-01			繪圖 DRAWN	Kilin 2017/10/02	
圖號 DRAWING NO.	GN011-KL120	版本 REV.	C	核對 CHECKED	Jason 2017/10/02	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2017/10/02	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		